



PondSeal®



DESCRIPTION

Swell Clay is an all natural Monmorillonate (Hydrated Sodium Aluminosilicate)

APPLICATION

- Soil Sealant
- Reservoirs
- Municipal Landfills
- Sanitation Lagoons
- Hazardous Storage
- Tailings Ponds
- Leach Pads
- Canals
- Tank Farms
- Ponds

TYPICAL PROPERTIES

Color: Tan/red
Density: 95 lbs ft³ (compact)
pH: 8.5 - 9.0
Swell: 19 cc
Moisture: 8-12 wt. %

SIEVE ANALYSIS

This analysis is typical, variations can apply

Screen mesh	% Passing
+4	19
+20	37
+20	49
+200	95

ADVANTAGES

- 100% Natural
- Ultra low permeability barrier
- Wide range of use
- Great containment barrier
- Mixes quickly and easily
- Excellent hard water performance

MIXING

The percent of PondSeal used should be determined through permeability testing and user specification requirements. Permeability testing is available at Western Clay upon request.

PACKAGING

PondSeal is available in 50 lb plastic bags (60 bags per pallet), and is also available in 3,000 lb. super sacks and bulk shipments.

To the best of our knowledge and belief, the above information is accurate. Because the conditions of handling and use are beyond our control, we cannot guarantee results, and assume no liability for damages incurred in using our product