



Swell Clay 200

DESCRIPTION

Swell Clay 200 is an all natural Montmorillonate (Hydrated Sodium Aluminosilicate)

APPLICATION

- Anti-Caking Agent
- Feed Pellet Binder
- General Use

TYPICAL PROPERTIES

Product Specification	Typical SURESEAL
Color	Tan/Red
Density	70 lbs ft ³ (compact)
PH	8.5 to 9.0
Moisture	6-12 wt.%

SIEVE ANALYSIS

This analysis is an average, variations can apply

SCREEN MESH	% PASSING
40	90
80	60
100	50
200	30

TYPICAL ELEMENTS

Aluminum	80,300	Gadolinium	11.9	Scandium	4.9
Antimony	29	Gallium	5	Silicon	51,450
Barium	452	Germanium	5	Silver	0.5
Beryllium	3.8	Iodine	24	Sodium	28,900
Boron	19	Iron	6,370	Strontium	54
Bromine	6.1	Lanthanum	30	Sulfur	1,500
Cadmium	0.16	Lead	0.38	Tellurium	0.43
Calcium	17,425	Lithium	168	Thallium	0.66
Carbon	29,00	Magnesium	39,000	Thorium	3
Cerium	5	Manganese	880	Thulium	1.1
Cesium	1	Neodymium	55	Tin	4.13
Chloride	76,500	Nickel	5.7	Titanium	1,465
Chromium	4	Phosphorus	35	Vanadium	462
Cobalt	2.5	Potassium	8,600	Ytterbium	2.4
Copper	12	Praseodymium	20	Yttrium	14.7
Dysprosium	4.6	Rhenium	2.13	Zinc	105
Fluoride	18	Samarium	6.5	Zirconium	61

PAKAGING

PONDSEAL 20 is available in BULK and 3,000 lb. BULK BAGS

AVAILABILITY

To order PONDSEAL 20 please contact us at 1-866-440-2529